Storefront Gates The Original Galvanized Steel Gate





Each Gate is Custom Manufactured to Protect Openings of any Size

- Protect property and merchandise
- Prevent unauthorized access
- Guard against vandalism
- Maintenance-free galvanized steel construction
- Gates ship in 7-14 business days
- Custom powder coated colors available
- 100% made in America



The Preferred Security Gate Since 1962


Storefront Folding Gates

Hybrid Gates (Maximum-Duty)


Designed with a continuous frame, utilizing vertical bars and traditional scissor style webbing, Hybrid Gates provide total coverage and maximum security. Available in single or pair, each gate is custom manufactured to protect openings of any size.

Specifications


Finish: Galvanized, Powder Coat Colors Available Webbing: ³/₈" x ³/₄" 14-gauge Steel Vertical Channel: 11/4" x 5%" 14-gauge C-channel Trolley: 1" Steel Wheels **Top & Bottom Track:** 17/8" x 15/16" 11-gauge U-channel Hinge Bar: 1¹/₂" x 1¹/₈" 12-gauge Angle Iron Locking Bar: 1⁷/₈" x 1⁵/₁₆" 11-gauge U-channel Hasp: 3/16" Steel Welded to Frame* Rivets: 1/4" x 11/2" Steel *Padlock not included, Cylinder Lock optional




Fixed Top & Fold-Away Bottom Track Max Width 16' | Max Height 12'




Fold-Away Top & Bottom Tracks Max Width 16' | Max Height 7'9"



Fixed Top & Fold-Away Bottom Track Max Width 32' | Max Height 12'



Fold-Away Top & Bottom Tracks Max Width 16' | Max Height 7'9" TRACK OPTIONS



Fixed Top & Fold-Away Bottom Track Drawing depicts a single gate



Fold-Away Top & Bottom Tracks Drawing depicts a single gate


Scissor Gates (Heavy-Duty & Extra Heavy Duty)

Gates are designed to secure areas wider than 20' and can be used to protect openings spanning several hundred feet. Scissor Storefront Gates are engineered to be wall-mounted providing heavy-duty security. Use optional top and/or bottom tracks for extra heavy-duty security.

Specifications

Finish: Galvanized, Powder Coat Colors Available Webbing: ³/₈" x ³/₄" 14-gauge Steel Frame: 1¹/₂" x 1¹/₂" 12-Gauge Angle Iron Trolley: 2" Diameter Zinc Steel Wheels Mounting Bracket: 21/2" x 7" L-bracket, Zinc Plated Hasp: 3/16" Steel Welded to Frame* Minimum Gate Height: 34"


*Padlock not included, Cylinder Lock optional




FIXED TOP TRACK Unlimited Width | Max Height 12'



FIXED BOTTOM TRACK Max Width 6' | Max Height 8'6"



FIXED TOP TRACK Unlimited Width | Max Height 12'



FIXED BOTTOM TRACK Max Width 12' | Max Height 8'6"





FIXED TOP TRACK Drawing depicts a single gate



FIXED BOTTOM TRACK Drawing depicts a single gate

Sold Exclusively by IEP Authorized Dealers





The Preferred Security Gate Since 1962